




◆ **MODEL 型式**
COD10



◆ **CONTROL PORT(S) 動作形式**

Standard Type 標準型

TS Type TS型
(Only for DC 僅適用於DC)




◆ **SPECIFICATIONS 規格**

Model Number 型式號碼	Voltage (V) 電壓			Holding Current (A) 固定電流	Weight 重量 Kg
	Source Rated 最大值	HZ 頻率	Range 範圍		
COD10-A1-*	RAC110V	50	100~120	0.19	0.34 (0.75 lbs)
		60			
COD10-A2-*	RAC220V	50	200~240	0.1	
		60			
COD10-D1-*	DC12V	—	10.9~13.2	1.7	
COD10-D2-*	DC24V	—	21.8~26.4	0.9	

- Above value based on temperature 30° C, electric voltage allowance 10%. 以上數據基礎為溫度30, 電壓容許度10%。
- Coil - COD10 series application for VWE-10 series .
線圈 - COD10 系列適用於 VWE-10 系列。

◆ **HOW TO ORDER 編號說明**



1 VALVE SERIES 系列名稱
COD = COIL 線圈

2 SUBPLATE MOUNTING SIZE
Size : 10 稱呼口徑


3 TYPE OF COIL 線圈類型

- A1: RAC110V 60/50HZ
- A2: RAC220V 60/50HZ
- D1: DC12V
- D2: DC24V


- RAC inner part does not include bridge rectifier, need to match with GDA3L9T250 connector (See Appendixes-E).
RAC內部不含橋式整流器,需搭配GDA3L9T250 接頭(見附錄E)

4 WIRING TYPE 接線型式

H: WIRING BOX TYPE (DIN 43650-A / ISO4400)
H: 接線盒式 (DIN 43650-A / ISO4400)




X: DOUBLE LEAD
X: 雙接線方式




AS: DUAL SPADES (SAE J858a)
AS: 雙扁形接頭 (SAE J858a)




K: KOSTAL M27x1.0



S: AMP SUPERSEAL-V



D: DEUTSCH DT04-2P-V



5 CONTROL PORT(S) 動作形式

Non: Standard 無記號: 標準型
TS: Transient Voltage-Suppression Diode (Only for DC) TS: 電壓抑制二極體 (僅適用於DC)

◆ **AVAILABLE WIRING TYPE FOR COIL TYPE**
線圈適用的接線型式

WIRING TYPE 接線型式	H	X	AS	K	S	D
A1: RAC110V	✓	—	—	—	—	—
A2: RAC220V	✓	—	—	—	—	—
D1: DC12V	✓	✓	✓	✓	✓	✓
D2: DC24V	✓	✓	✓	✓	✓	✓

◆ **DIMENSIONS 外型尺寸圖**

