


◆ **MODEL 型 式**

**VLS-10**




◆ **DESCRIPTION 說明**

Shuttle Valves, cartridge-style hydraulic check valve, for use in blocking circuits where a priority of flow/direction is given to a higher pressure circuit over a lower one.

梭動閥，插入式油壓止逆閥，在流量/方向被優先供應至較高的壓力迴路時，用於阻擋低壓迴路。

◆ **PERFORMANCE 特性曲線**  
(Cartridge Only)



◆ **SPECIFICATIONS 規 格**

Model Number 型式號碼	Operating Pressure 操作壓力 bar	Flow 流量 lpm	Weight 重量 Kg
VLS-10	350 (5076psi)	30 (7.93 gpm)	0.09 (0.20 lbs)
<b>Fluid Type</b> 流體型式		ISO VG 32, 46, 68	
<b>Viscosity</b> 黏性 cSt		10~400 (59~1854 SSU)	
<b>Operating Temperature</b> 操作溫度 °C		-15~70 (-5~158°F)	
<b>Contamination Level</b> 污染標準		ISO4406. 21/19/16 NAS1638,10	

◆ **HOW TO ORDER 編號說明**

<b>1</b>	<b>2</b>
<b>VLS</b>	<b>10</b>


**1 VALVE SERIES** 系列名稱

VLS= CARTRIDGE SHUTTLE VALVES  
插入式梭動閥

**2 PORTING** 閥口

Size: 10  
Cavity 孔口: CS10-3N  
See Page Appendixes-A\_002  
見附錄A\_002 頁面

◆ **CONTROL PORT(S) 動作形式**



◆ **DIMENSIONS 外型尺寸圖**

