




◆ **MODEL 型式**
COB08



◆ **CONTROL PORT(S) 動作形式**

Standard Type 標準型

TS Type TS型
(Only for DC 僅適用於DC)




◆ **SPECIFICATIONS 規格**

Model Number 型式號碼	Voltage (V) 電壓			Resistance 電阻 Ω	Holding Current (A) 固定電流	Power (W) 功率	Weight 重量 Kg
	Source Rated 最大値	HZ 頻率	Range 範圍				
COB08-A1-*	RAC110V	50	100~120	570	0.19	17	0.20 (0.44 lbs)
		60					
COB08-A2-*	RAC220V	50	200~240	2323	0.1	17	
		60					
COB08-D1-*	DC12V	—	10.9~13.2	8.7	1.7	17	
COB08-D2-*	DC24V	—	21.8~26.4	3.2	0.9	17	

- Above value based on temperature 30° C, electric voltage allowance 10%. 以上數據基礎為溫度30, 電壓容許度10%。
- Coil - COB08 series application for VSE .VSV series , VWE08.
線圈 - COB08 系列適用於 VSE.VSV系列 , VWE08.

◆ **HOW TO ORDER 編號說明**



1 VALVE SERIES 系列名稱
COB = COIL (SEMICIRCLE)
線圈 (半圓形)


2 SUBPLATE MOUNTING SIZE
Size : 08 稱呼口徑

3 TYPE OF COIL 線圈類型
A1 : RAC110V 60/50HZ
A2 : RAC220V 60/50HZ
D1 : DC12V
D2 : DC24V


- RAC inner part does not include bridge rectifier, need to match with GDA3L9T250 connector (See Appendixes-E).
RAC內部不含橋式整流器,需搭配GDA3L9T250 接頭(見附錄E)

4 WIRING TYPE 接線型式

H: WIRING BOX TYPE
(DIN 43650-A / ISO4400)
H: 接線盒式 (DIN 43650-A / ISO4400)




X: DOUBLE LEAD
X: 雙接線方式




AS: DUAL SPADES (SAE J858a)
AS: 雙扁形接頭 (SAE J858a)




K: KOSTAL M27x1.0



S: AMP SUPERSEAL-V



D: DEUTSCH DT04-2P-V



5 CONTROL PORT(S) 動作形式

Non: Standard 無記號 : 標準型
TS: Transient Voltage-Suppression Diode (Only for DC) TS: 電壓抑制二極體 (僅適用於DC)

◆ **AVAILABLE WIRING TYPE FOR COIL TYPE**

線圈適用的接線型式

WIRING TYPE 接線型式	H	X	AS	K	S	D
A1: RAC110V	✓	—	—	—	—	—
A2: RAC220V	✓	—	—	—	—	—
D1: DC12V	✓	✓	✓	✓	✓	✓
D2: DC24V	✓	✓	✓	✓	✓	✓

◆ **DIMENSIONS 外型尺寸圖**

